

TA150WA12LED65B15R1
No-Load Electronic Transformer



Efficiency	>85%
Power Factor	>0.98
Case TC	90C° Max.
Protection	Input/Output
Storage	-30°C/+90°C
Humidity	95% RH Max.
IP Rating	IP60
Class	Class 2 Power Supply
Dimming	ELV, Optional 0-10V



FEATURES

- No minimum load technology, works with both Halogen & LED AC Loads
- Dimmable with ELV type dimmers
- Isolated output power per NEC and UL safety requirements
- UL recognized/listed Class 2 power supply, meets UL 2108 requirements
- Low EMI; meets FCC title 15 Class B, conducted emission requirements
- Auto-reset; Short circuit, Overload and Thermal protection
- Soft start
- Low profile, small compact design to fit in most enclosures
- Available with optional UL Listed indoor and Outdoor remote enclosures

ELECTRICAL SPECIFICATIONS

Model Number	Input Voltage	Watts	Input Current	Output Voltage	Load Type	Dimming
TA150WA12LED65B15R1	120V AC 1.3A 50/60Hz	150W	1.3A	12V AC	LED Strips, AC LED Bulbs, Incandescent & Halogen	ELV, Optional 0-10V

MECHANICAL SPECIFICATIONS

Form Factor	Dimensions
"R" Standard	92.1 mm (OD) x 14mm (ID), 32.6mm

